

Dimensions(mm)

Centro flange		D1	D2	D3	D4	L1	L2	L3	L4	Clamping wrench	Adjustment bolt (wrench)	Kg.
FL58/GCT6	●	6	25	58	-	42	-	31	25	TR-4.0	-	0.4
FL58/GCT8	●	8	28	58	-	42	-	31	25	TR-4.0	-	0.4
FL58/GCT10	●	10	30	58	-	42	-	38	25	TR-4.0	-	0.4
FL58/GCT12	●	12	31	58	-	42	-	43	25	TR-4.0	-	0.4
FL68/GCT20	●	20	41.5	68	-	48	-	48	31	TR-4.0	-	0.7

Connection holder												
ST25/D58-CONN	●	25	58	-	-	60	20	-	-	-	M6x1.0(T-3.0)	0.6
ST25/D68-CONN	●	25	68	-	-	60	20	-	-	-	M6x1.0(T-3.0)	0.7
ST32/D58-CONN	●	32	58	-	-	70	20	-	-	-	M6x1.0(T-3.0)	0.8
ST32/D68-CONN	●	32	68	-	-	70	20	-	-	-	M6x1.0(T-3.0)	0.9
ST40/D58-CONN	●	40	58	-	-	70	20	-	-	-	M6x1.0(T-3.0)	1.0
ST40/D68-CONN	●	40	68	-	-	70	20	-	-	-	M6x1.0(T-3.0)	1.1

Availability: ● Stock ▲ Short lead time ○ Made to order

- »h6 shank tools must be used.
- »T-wrench is must be ordered separately.
(GRIP torque wrench is recommended.)
- »All products center through coolant system.
- »Additional sizes and special designs available on request.
- ⚠ The minimum tool depth must be observed.



