


Dual Contact Type

BT-DC type holder can be used for BT double contact spindle and also used for BT standard spindle.




Dimensions(mm)

BT30DC		D1	D2	D3	D4	L1	L2	L3	L4	Clamping wrench	Adjustment bolt (wrench)	Kg.
BT30DC/GMR6/70	●	6	23	26	44.5	70	37.5	27.5	28	TR-4.0	M5x0.8(T-2.5)	0.7
BT30DC/GMR8/70	●	8	25	28	44.5	70	37.5	27.5	28	TR-4.0	M6x1.0(T-3.0)	0.8
BT30DC/GMR10/75	●	10	27	30	44.5	75	42.5	32.5	36	TR-4.0	M8x1.0(T-4.0)	0.8
BT30DC/GMR12/75	●	12	29	32	44.5	75	47.5	37.5	36	TR-4.0	M10x1.0(T-5.0)	0.9
BT30DC/GMR14/85	●	14	31	34	44.5	85	47.5	37.5	44	TR-4.0	M10x1.0(T-5.0)	0.9
BT30DC/GMR16/90	●	16	35	38	44.5	90	52.5	42.5	48	TR-4.0	M12x1.0(T-6.0)	1.0
BT30DC/GMR18/90	●	18	37	40	44.5	90	52.5	42.5	48	TR-4.0	M12x1.0(T-6.0)	1.0
BT30DC/GMR20/90	●	20	39	42	44.5	90	52.5	42.5	48	TR-4.0	M12x1.0(T-6.0)	1.1

Availability: ● Stock ▲ Short lead time ○ Made to order

- »h6 shank tools must be used.
- »Tool length can be adjusted up to 10mm.
- »T-wrench is must be ordered separately.
(GRIP torque wrench is recommended.)
- »All products center through coolant system.
- »Additional sizes and special designs available on request.
- »BT-DC type holder can be used for BT double contact spindle and also used for BT standard spindle.

⚠ The minimum tool depth must be observed.



BT30DC