

Dimensions(mm)

HSK-C63		D1	D2	D3	D4	L1	L2	L3	L4	Clamping wrench	Adjustment bolt (wrench)	Kg.
HSK-C63/GMR6/60	○	6	23	26	63	60	37.5	27.5	24	TR-4.0	M5x0.8(T-2.5)	0.9
HSK-C63/GMR8/60	○	8	25	28	63	60	37.5	27.5	24	TR-4.0	M6x1.0(T-3.0)	1.0
HSK-C63/GMR10/65	○	10	27	30	63	65	42.5	32.5	35	TR-4.0	M8x1.0(T-4.0)	1.1
HSK-C63/GMR12/75	●	12	29	32	63	75	47.5	37.5	40	TR-4.0	M10x1.0(T-5.0)	1.1
HSK-C63/GMR14/75	○	14	31	34	63	75	47.5	37.5	40	TR-4.0	M10x1.0(T-5.0)	1.2
HSK-C63/GMR16/80	○	16	35	38	63	80	52.5	42.5	46	TR-4.0	M12x1.0(T-6.0)	1.2
HSK-C63/GMR18/80	○	18	37	40	63	80	52.5	42.5	47	TR-4.0	M12x1.0(T-6.0)	1.2
HSK-C63/GMR20/80	●	20	39	42	63	80	52.5	42.5	48	TR-5.0	M16x1.0(T-6.0)	1.3
HSK-C63/GMR25/95	○	25	53	57	63	95	61	51	59	TR-5.0	M16x1.0(T-6.0)	2.0
HSK-C63/GMR32/100	○	32	58	63	63	100	65	55	-	TR-5.0	M16x1.0(T-6.0)	2.1

Availability: ● Stock ▲ Short lead time ○ Made to order

- »h6 shank tools must be used.
- »Tool length can be adjusted up to 10mm.
- »T-wrench is must be ordered separately.
(GRIP torque wrench is recommended.)
- »Coolant tube as an option.
- »All products center through coolant system.
- »Additional sizes and special designs available on request.

⚠ The minimum tool depth must be observed.

