

 Dimensions(mm)

| SK40            |   | D1 | D2 | D3 | D4 | L1   | L2   | L3   | L4 | Clamping<br>wrench | Adjustment bolt<br>(wrench) | Kg. |
|-----------------|---|----|----|----|----|------|------|------|----|--------------------|-----------------------------|-----|
| SK40/GMR6/80.5  | ● | 6  | 23 | 26 | 50 | 80.5 | 37.5 | 27.5 | 44 | TR-4.0             | M5x0.8(T-2.5)               | 1.3 |
| SK40/GMR6/110   | ● | 6  | 23 | 26 | 50 | 110  | 37.5 | 27.5 | 44 | TR-4.0             | M5x0.8(T-2.5)               | 1.7 |
| SK40/GMR8/80.5  | ● | 8  | 25 | 28 | 50 | 80.5 | 37.5 | 27.5 | 44 | TR-4.0             | M6x1.0(T-3.0)               | 1.3 |
| SK40/GMR8/110   | ● | 8  | 25 | 28 | 50 | 110  | 37.5 | 27.5 | 44 | TR-4.0             | M6x1.0(T-3.0)               | 1.7 |
| SK40/GMR10/80.5 | ● | 10 | 27 | 30 | 50 | 80.5 | 42.5 | 32.5 | 44 | TR-4.0             | M8x1.0(T-4.0)               | 1.3 |
| SK40/GMR10/110  | ● | 10 | 27 | 30 | 50 | 110  | 42.5 | 32.5 | 44 | TR-4.0             | M8x1.0(T-4.0)               | 1.8 |
| SK40/GMR12/80.5 | ● | 12 | 29 | 32 | 50 | 80.5 | 47.5 | 37.5 | 44 | TR-4.0             | M10x1.0(T-5.0)              | 1.3 |
| SK40/GMR12/110  | ● | 12 | 29 | 32 | 50 | 110  | 47.5 | 37.5 | 44 | TR-4.0             | M10x1.0(T-5.0)              | 1.8 |
| SK40/GMR14/80.5 | ● | 14 | 31 | 34 | 50 | 80.5 | 47.5 | 37.5 | 44 | TR-4.0             | M10x1.0(T-5.0)              | 1.3 |
| SK40/GMR14/110  | ● | 14 | 31 | 34 | 50 | 110  | 47.5 | 37.5 | 44 | TR-4.0             | M10x1.0(T-5.0)              | 1.8 |
| SK40/GMR16/80.5 | ● | 16 | 35 | 38 | 50 | 80.5 | 52.5 | 42.5 | 48 | TR-4.0             | M12x1.0(T-6.0)              | 1.4 |
| SK40/GMR16/110  | ● | 16 | 35 | 38 | 50 | 110  | 52.5 | 42.5 | 48 | TR-4.0             | M12x1.0(T-6.0)              | 1.9 |
| SK40/GMR18/80.5 | ● | 18 | 37 | 40 | 50 | 80.5 | 52.5 | 42.5 | 48 | TR-4.0             | M12x1.0(T-6.0)              | 1.4 |
| SK40/GMR18/110  | ● | 18 | 37 | 40 | 50 | 110  | 52.5 | 42.5 | 48 | TR-4.0             | M12x1.0(T-6.0)              | 1.9 |
| SK40/GMR20/80.5 | ● | 20 | 39 | 42 | 50 | 80.5 | 52.5 | 42.5 | 48 | TR-5.0             | M16x1.0(T-6.0)              | 1.4 |
| SK40/GMR20/110  | ● | 20 | 39 | 42 | 50 | 110  | 52.5 | 42.5 | 48 | TR-5.0             | M16x1.0(T-6.0)              | 2.0 |
| SK40/GMR25/80.5 | ● | 25 | 51 | 55 | 66 | 80.5 | 61   | 51   | 26 | TR-5.0             | M16x1.0(T-6.0)              | 1.8 |
| SK40/GMR32/80.5 | ● | 32 | 58 | 62 | 80 | 80.5 | 65   | 55   | 26 | TR-5.0             | M16x1.0(T-6.0)              | 2.2 |

Availability: ● Stock ▲ Short lead time ○ Made to order