

= Dimensions(mm)

HSK-A100		D1	D2	D3	D4	L1	L2	L3	L4	Clamping wrench	Radial Adjustment (wrench)	Kg.
HSK-A100/GPS6/85	●	6	23	26	50	85	37.5	27.5	33	TR-4.0	T-2.0	2.8
HSK-A100/GPS8/85	●	8	25	28	50	85	37.5	27.5	33	TR-4.0	T-2.0	2.8
HSK-A100/GPS10/90	●	10	27	30	50	90	42.5	32.5	36	TR-4.0	T-2.0	2.8
HSK-A100/GPS12/95	●	12	29	32	50	95	47.5	37.5	40	TR-4.0	T-2.0	2.8
HSK-A100/GPS14/95	●	14	31	34	50	95	47.5	37.5	46	TR-4.0	T-3.0	2.9
HSK-A100/GPS16/100	●	16	35	38	50	100	52.5	42.5	51	TR-4.0	T-3.0	2.9
HSK-A100/GPS18/100	●	18	37	40	50	100	52.5	42.5	52	TR-4.0	T-3.0	3.0
HSK-A100/GPS20/105	●	20	39	42	50	105	52.5	42.5	58	TR-5.0	T-3.0	3.0
HSK-A100/GPS25/115	●	25	53	57	63	115	61	51	60	TR-5.0	T-3.0	3.7
HSK-A100/GPS32/120	●	32	58	63	75	120	65	55	68	TR-5.0	T-3.0	4.1

Availability: ● Stock ▲ Short lead time ○ Made to order

- »h6 shank tools must be used.
 - »Tool length can be adjusted up to 10mm.
 - »T-wrench is must be ordered separately.
(GRIP torque wrench is recommended.)
 - »Data carrier and Coolant tube as an option.
 - »All products center through coolant system.
 - »Additional sizes and special designs available on request.
- ⚠ The minimum tool depth must be observed.

