

Dimensions(mm)

HSK-A100		D1	D2	D3	D4	L1	L2	L3	L4	Clamping wrench	Adjustment bolt (wrench)	Kg.
HSK-A100/GSL6/180	●	6	16	24	50	180	37.5	27.5	120	TR-4.0	M5x0.8(T-2.5)	3.0
HSK-A100/GSL8/180	●	8	18	26	50	180	37.5	27.5	120	TR-4.0	M6x1.0(T-3.0)	3.1
HSK-A100/GSL10/180	○	10	20	28	50	180	42.5	32.5	120	TR-4.0	M8x1.0(T-4.0)	3.1
HSK-A100/GSL12/180	●	12	22	30	50	180	47.5	37.5	120	TR-4.0	M10x1.0(T-5.0)	3.2
HSK-A100/GSL14/180	○	14	24	32	50	180	47.5	37.5	121	TR-4.0	M10x1.0(T-5.0)	3.2
HSK-A100/GSL16/180	○	16	26	34	50	180	52.5	42.5	121	TR-4.0	M12x1.0(T-6.0)	3.3
HSK-A100/GSL18/180	○	18	28	36	50	180	52.5	42.5	122	TR-4.0	M12x1.0(T-6.0)	3.4
HSK-A100/GSL20/180	●	20	30	38	50	180	52.5	42.5	122	TR-4.0	M16x1.0(T-6.0)	3.4

Availability: ● Stock ▲ Short lead time ○ Made to order

- »h6 shank tools must be used.
- »Tool length can be adjusted up to 10mm.
- »T-wrench is must be ordered separately.
(GRIP torque wrench is recommended.)
- »Data carrier and Coolant tube as an option.
- »All products center through coolant system.
- »Additional sizes and special designs available on request.

⚠ The minimum tool depth must be observed.

