

Front Type




Dimensions(mm)

ST16	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST16-GST3-50	3	16	-	50	17.5	24	28	-		TR-3.0	P01 /P03
ST16-GST3.175-50	3.175	16	-	50	17.5	24	28	-		TR-3.0	
ST16-GST4-50	4	16	-	50	21	26	28	-		TR-3.0	

ST20	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST20-GST3-110	3	20	-	110	17.5	24	40	-		TR-3.0	BO12 /20 /S20 SERIES
ST20-GST4-110	4	20	-	110	21	26	40	-		TR-3.0	
ST20-GST6-110	6	20	-	110	23	29	52	-		TR-3.0	
ST20-GST8-110	8	20	-	110	28	34	52	-		TR-3.0	

ST25	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST25-GST3-110	3	25	-	110	17.5	24	40	-		TR-4.0	32 SERIES
ST25-GST4-110	4	25	-	110	21	26	40	-		TR-4.0	
ST25-GST6-110	6	25	-	110	23	29	52	-		TR-4.0	
ST25-GST8-110	8	25	-	110	28	34	52	-		TR-4.0	
ST25-GST10-110	10	25	-	110	29.5	36	55	-		TR-4.0	
ST25-GST12-110	12	25	-	110	31.5	38	58	-		TR-4.0	



ST16/ ST20/ ST25

Back Type



≡ Dimensions(mm)

ST20	D1	D2	D3	L1	L2	L3	L4	L5	L6	Wrench	Type of machine
ST20-GST4-40/75	4	20	19	75	21	26	46	14	40	TR-4.0	BO12 /20 /S20 SERIES
ST20-GST6-40/75	6	20	20	75	23	29	51	15	40	TR-4.0	
ST20-GST8-40/75	8	20	23	75	28	36	51	16	40	TR-4.0	
ST20-GST10-40/75	10	20	27	75	29.5	36	56	17	40	TR-4.0	

ST25	D1	D2	D3	L1	L2	L3	L4	L5	L6	Wrench	Type of machine
ST25-GST4-60/95	4	25	19	95	21	26	46	14	60	TR-4.0	32 SERIES
ST25-GST6-60/95	6	25	20	95	23	29	51	15	60	TR-4.0	
ST25-GST8-60/95	8	25	23	95	28	34	51	16	60	TR-4.0	
ST25-GST10-60/95	10	25	27	95	29.5	36	56	17	60	TR-4.0	
ST25-GST12-60/95	12	25	29	95	31.5	38	56	18	60	TR-4.0	


»h6 shank tools must be used.

»T-wrench is must be ordered separately.

»The inner diameter 8 and 12 can be used with various tools by using the hydro-sleeve.

»All products center through coolant system.(All item Coolant M6x1.0)

»Additional sizes and special designs available on request.



ST20/ ST25

Front Type

TORNOS

= Dimensions(mm)

ST16	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST16-GST3-50	3	16	-	50	17.5	24	28	-		TR-3.0	MICRO 7/8
ST16-GST3.175-50	3.175	16	-	50	17.5	24	28	-		TR-3.0	
ST16-GST4-50	4	16	-	50	21	26	28	-		TR-3.0	
ST16-GST3-90	3	16	-	90	17.5	24	40	-		TR-3.0	SWISS NANO SERIES
ST16-GST3.175-90	3.175	16	-	90	17.5	24	40	-		TR-3.0	
ST16-GST4-90	4	16	-	90	21	26	40	-		TR-3.0	
ST16-GST6-90	6	16	-	90	23	29	37	-		TR-3.0	

ST20	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST20-GST3-110	3	20	-	110	17.5	24	40	-		TR-3.0	GAMMA20
ST20-GST4-110	4	20	-	110	21	26	40	-		TR-3.0	
ST20-GST6-110	6	20	-	110	23	29	52	-		TR-3.0	
ST20-GST8-110	8	20	-	110	28	34	52	-		TR-3.0	

ST22	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST22-GST3-110	3	22	-	110	17.5	24	40	-		TR-4.0	DELTA 20 GAMMA 20
ST22-GST4-110	4	22	-	110	21	26	40	-		TR-4.0	
ST22-GST6-110	6	22	-	110	23	29	52	-		TR-4.0	
ST22-GST8-110	8	22	-	110	28	34	52	-		TR-4.0	
ST22-GST10-110	10	22	-	110	29.5	36	55	-		TR-4.0	

ST25	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST25-GST3-110	3	25	-	110	17.5	24	40	-		TR-4.0	DECO (7/10/13/20)
ST25-GST4-110	4	25	-	110	21	26	40	-		TR-4.0	
ST25-GST6-110	6	25	-	110	23	29	52	-		TR-4.0	
ST25-GST8-110	8	25	-	110	28	34	52	-		TR-4.0	
ST25-GST10-110	10	25	-	110	29.5	36	55	-		TR-4.0	
ST25-GST12-110	12	25	-	110	31.5	38	58	-		TR-4.0	

Back Type

TORNOS

= Dimensions(mm)

ST20	D1	D2	D3	L1	L2	L3	L4	L5	L6	Wrench	Type of machine
ST20-GST4-40/75	4	20	19	75	21	26	46	14	40	TR-4.0	GT13/ GT26 GAMMA20
ST20-GST6-40/75	6	20	20	75	23	29	51	15	40	TR-4.0	
ST20-GST8-40/75	8	20	23	75	28	36	51	16	40	TR-4.0	
ST20-GST10-40/75	10	20	27	75	29.5	36	56	17	40	TR-4.0	

ST25	D1	D2	D3	L1	L2	L3	L4	L5	L6	Wrench	Type of machine
ST25-GST4-60/95	4	25	19	95	21	26	46	14	60	TR-4.0	DECO (7/10/13/20)
ST25-GST6-60/95	6	25	20	95	23	29	51	15	60	TR-4.0	
ST25-GST8-60/95	8	25	23	95	28	34	51	16	60	TR-4.0	
ST25-GST10-60/95	10	25	27	95	29.5	36	56	17	60	TR-4.0	
ST25-GST12-60/95	12	25	29	95	31.5	38	56	18	60	TR-4.0	


»h6 shank tools must be used.

»T-wrench is must be ordered separately.


»The inner diameter 8 and 12 can be used with various tools by using the hydro-sleeve.

»All products center through coolant system.(All item Coolant M6x1.0)

»Additional sizes and special designs available on request.



ST16/ ST20/ ST22/ ST25



ST20/ ST25

Front Type




Dimensions(mm)

ST20	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST20-GST3-110	3	20	-	110	17.5	24	40	-		TR-3.0	SL12H
ST20-GST4-110	4	20	-	110	21	26	40	-		TR-3.0	
ST20-GST6-110	6	20	-	110	23	29	52	-		TR-3.0	
ST20-GST8-110	8	20	-	110	28	34	52	-		TR-3.0	

ST25	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST25-GST3-110	3	25	-	110	17.5	24	40	-		TR-4.0	20 SERIES
ST25-GST4-110	4	25	-	110	21	26	40	-		TR-4.0	
ST25-GST6-110	6	25	-	110	23	29	52	-		TR-4.0	
ST25-GST8-110	8	25	-	110	28	34	52	-		TR-4.0	
ST25-GST10-110	10	25	-	110	29.5	36	55	-		TR-4.0	
ST25-GST12-110	12	25	-	110	31.5	38	58	-		TR-4.0	

ST32	D1	D2	D3	L1	L2	L3	L4	L5	Shape	Wrench	Type of machine
ST32-GST3-110	3	32	-	110	17.5	24	40	-		TR-4.0	32 SERIES
ST32-GST4-110	4	32	-	110	21	26	40	-		TR-4.0	
ST32-GST6-110	6	32	-	110	23	29	52	-		TR-4.0	
ST32-GST8-110	8	32	-	110	28	34	52	-		TR-4.0	
ST32-GST10-110	10	32	-	110	29.5	36	55	-		TR-4.0	
ST32-GST12-110	12	32	-	110	31.5	38	58	-		TR-4.0	



ST20/ ST25/ ST32