

Dimensions(mm)

SK40		D1	D2	D3	D4	L1	L2	L3	L4	Clamping wrench	Adjustment bolt (wrench)	Kg.
SK40/GZF12/90	○	12	29	32	50	90	53	43	53	TR-4.0	M10x1.0(T-5.0)	1.4
SK40/GZF20/90	○	20	39	42	50	90	58	48	58	TR-4.0	M16x1.0(T-6.0)	1.5

SK50		D1	D2	D3	D4	L1	L2	L3	L4	Clamping wrench	Adjustment bolt (wrench)	Kg.
SK50/GZF12/90	○	12	29	32	50	90	53	43	53	TR-4.0	M10x1.0(T-5.0)	3.4
SK50/GZF20/110	○	20	39	42	50	110	58	48	68	TR-5.0	M16x1.0(T-6.0)	3.6
SK50/GZF32/115	○	32	58	62	62	115	71	61	-	TR-5.0	M16x1.0(T-6.0)	4.9

Availability: ● Stock ▲ Short lead time ○ Made to order

- »h6 shank tools must be used.
 - »Tool length can be adjusted up to 10mm.
(If you use the ZERO-FIT function, you cannot use the adjust screw.)
 - »T-wrench is must be ordered separately.
(GRIP torque wrench is recommended.)
 - »If you use the ZERO-FIT function, you cannot use the hydro-sleeve.
 - »All products center through coolant system.
 - »Additional sizes and special designs available on request.
- ⚠ The minimum tool depth must be observed.

